



PETROMIN Grease MP series is a superior multi-purpose grease suitable for a wide range of low to moderate service in automotive and industrial applications. It is formulated with higher viscosity base oil to ensure better wear protection. It provides enhanced protection against rust and corrosion, resulting in increased machinery life.

## Benefits

- Lithium hydroxy-stearate thickener improves structural stability and reduces re-greasing requirement.
- Provides better wear and component protection for enhanced machinery life.
- Advanced formulation ensures superior rust and corrosion protection.
- Ideal grease for low to moderate service, speed, and temperature conditions.

## Meets/Exceeds

- NLGI 2 / NLGI 3

## Applications

- Multi-purpose application for Automotive use in passenger cars, trucks, farm tractors and mobile equipment.
- Lubrication of automotive chassis points, universal joints, wheel bearings, and ball joints.
- Wide range of Industrial applications such as general lubrication of roller bearings and sliding bearings.
- Suitable for general industrial equipment, machine tools, and home appliances.

## Product Characteristics

Properties	Test Method	Unit	MP2	MP3
NLGI	ASTM D217	-	2	3
Appearance	Visual	-	Smooth & Homogeneous	
Color	Visual	-	Light Brown	
Thickener Type	-	-	Lithium	Lithium
Base Oil Viscosity @ 40 °C	ASTM D445	cSt	200	200
Base Oil Viscosity @ 100 °C	ASTM D445	cSt	17.5	17.5
Dropping Point	ASTM D2265	°C	200	205
Worked Penetration @ 25 °C	ASTM D217	mm/10	275	230
Oil Separation, 42 Hrs. 40 °C	IP 121	% mass	5.0	1.5
Operating Temperature	-	°C	-10 to 120	-10 to 120
<i>Product Code</i>			<i>001000</i>	<i>007000</i>

\* Information, test methods, figures are typical and conform to specification; minor variation may occur.

\* Refer Owner's Manual for the manufacturer's recommended performance level, NLGI grade and builder approval requirements.

\* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

