



PETROMIN Premium Motor Oil is a monograde engine lubricant for passenger cars and light-duty gasoline vehicles. It offers well-balanced oxidation stability and engine cleanliness. This product is suitable for legacy vehicles requiring API SJ or lower performance specification.

Benefits

- Effectively controls deposit formation at high temperatures.
- Protects against rust, wear, and sludge formation.
- Provides a fit-for-purpose lubrication solution for older-generation gasoline engines.

Meets/Exceeds

- API SJ

Applications

- Suitable for engines requiring API SJ or lower performance.
- Recommended for light-duty on-highway vehicles with monograde oil requirements.

Product Characteristics

Properties	Test Method	Unit	SAE 40
Density @ 15 °C	ASTM D4052	kg/L	0.8982
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	151.8
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	15.2
Viscosity Index	ASTM D2270	-	101
Flash Point, COC	ASTM D92	°C	254
Pour Point	ASTM D97	°C	-15
Total Base Number	ASTM D2896	mg KOH/g	6.5
<i>Product Code</i>			<i>106000</i>

* Information, test methods, figures are typical and conform to specification; minor variation may occur.

* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information

