



PETROMIN Petrocool (Green) series is a ready-to-use, pre-mixed engine coolant designed to deliver reliable performance and protection. It contains advanced Organic Additive Technology (OAT) that safeguards critical components commonly found in the cooling systems of gasoline and diesel engines. It is designed for light and medium duty automotive applications.

Benefits

- Improves cooling system efficiency and helps prevent deposit formation.
- Provides protection against freezing, overheating, and boil-over.
- Extended service life through advanced corrosion inhibitor technology.

Meets/Exceeds

- BS 6580

Applications

- Suitable for light- and medium-duty gasoline and diesel engines.
- Recommended for passenger cars, light commercial vehicles, and medium duty trucks.
- Ready-to-use premix coolant; requires no further dilution with water.

Product Characteristics

Properties	Test Method	Unit	40%	50%
Color	Visual	-	Green	Green
Freezing Point	ASTM D3321	°C	-28	-39
Equilibrium Boiling Point	ASTM D1120	°C	107	110
Glycol Concentration	ASTM D3306	%	40.0	50.0
Density at 20°C	ASTM D4052	kg/L	1.059	1.071
Reserve Alkalinity	ASTM D1211	ml	Report	Report
pH	ASTM D1287	-	8.0	8.1
<i>Product Code</i>			<i>110400</i>	<i>110500</i>

- * Information, test methods, figures are typical and conform to specification; minor variation may occur.
- * Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- * Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

