



PETROMIN Super HD 50 is a monograde engine lubricant for passenger cars and light-duty gasoline vehicles, offering well-balanced oxidation stability and engine cleanliness. It is suitable for legacy vehicles requiring API SJ or lower performance specifications.

Benefits

- Effective deposit formation at high temperatures.
- Protects against rust, wear, and sludge formation.
- Provides fit-for-purpose lubricant solution for older-generation gasoline engines.

Meets/Exceeds

- API SJ

Applications

- Suitable for legacy and older-generation gasoline engines requiring API SJ or lower performance.
- Recommended for light-duty on-highway vehicles with monograde oil requirement.

Product Characteristics

Properties	Test Method	Unit	HD 50 SJ
Density @ 15 °C	ASTM D4052	kg/L	0.8939
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	216.2
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	19.6
Viscosity Index	ASTM D2270	-	103
Flash Point, COC	ASTM D92	°C	260
Pour Point	ASTM D97	°C	-21
Total Base Number	ASTM D2896	mg KOH/g	6.7
<i>Product Code</i>			<i>115000</i>

- * Information, test methods, figures are typical and conform to specification; minor variation may occur.
- * Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- * Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

