



PETROMIN Super Bike 4T series is a superior performance, shear-stable, multigrade gasoline engine oil specifically formulated for modern four-stroke motorcycles and portable power equipment. It is engineered to deliver excellent protection for high-output engines operating under severe service conditions. The product meets API SL and JASO MA/MA2 specifications, ensuring superior clutch compatibility, oxidation stability, and wear protection.

Benefits

- Protects engine component (piston, cylinders, camshafts) against wear and scuffing extending engine life.
- Resists oil breakdown at high temperatures, reducing deposits formation and sludge.
- Safeguards engine parts from corrosion and rust in humid or wet conditions.
- Maintain film strength under heavy load or high-speed operation, protecting critical engine surfaces.

Meets/Exceeds

- API SL
- JASO MA2

Applications

- Suitable for air-and liquid-cooled four-stroke motorcycle engines.
- For engines with or without oil-immersed clutches, combined engine/transmission units, or with separate gearboxes, where a multigrade engine oil is specified.
- Compatible with motorcycles equipped with exhaust catalytic converters.

Product Characteristics

Properties	Test Method	Unit	SAE 10W-30	SAE 10W-40	SAE 20W-50
Density @ 15 °C	ASTM D4052	kg/L	0.8693	0.8681	0.8732
Kin. Viscosity at 40 °C	ASTM D445	cSt	77.2	99.7	166.7
Kin. Viscosity at 100 °C	ASTM D445	cSt	11.3	14.3	19.3
Viscosity Index	ASTM D2270	-	136	149	132
Flash Point, COC	ASTM D92	°C	234	234	266
Pour Point	ASTM D97	°C	-39	-36	-27
Total Base Number	ASTM D2896	mg KOH/g	5.6	5.6	5.6
<i>Product Code</i>			<i>125000</i>	<i>162000</i>	<i>130000</i>

* Information, test methods, figures are typical and conform to specification; minor variation may occur.

* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

