



PETROMIN Super Bike 20W-40 SL is a standard performance multigrade gasoline engine oil specifically formulated for modern four-stroke motorcycles. It is engineered to deliver excellent protection for high-output engines operating under severe service conditions. The product meets API SL and JASO MA/MA2 specifications, ensuring superior clutch compatibility, oxidation stability, and wear protection.

Benefits

- Protects engine, clutch, and gear against wear and scuffing extending engine and powertrain life.
- Resists oil breakdown at high temperatures, reducing deposits formation and sludge.
- Maintain film strength under heavy load or high-speed operation, protecting critical engine surfaces.

Meets/Exceeds

- API SL
- JASO MA2

Applications

- Suitable for air-and liquid-cooled four-stroke motorcycle engines.
- For engines with or without oil-immersed clutches, combined engine/transmission units, or with separate gearboxes, where a multigrade engine oil is specified.

Product Characteristics

Properties	Test Method	Unit	SAE 20W-40
Density @ 15 °C	ASTM D4052	kg/L	0.8754
Kin. Viscosity at 40 °C	ASTM D445	cSt	127.7
Kin. Viscosity at 100 °C	ASTM D445	cSt	15.0
Viscosity Index	ASTM D2270	-	120
Flash Point, COC	ASTM D92	°C	252
Pour Point	ASTM D97	°C	-30
Total Base Number	ASTM D2896	mg KOH/g	6.3
<i>Product Code</i>			137000

- * Information, test methods, figures are typical and conform to specification; minor variation may occur.
- * Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- * Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

