

NATIONAL SpeedX SPX5 10W-40

NATIONAL SpeedX SPX5 10W-40 is a synthetic technology engine oil suitable for both modern and legacy gasoline engines. Formulated with a high-performance additive system, it ensures reliable operation under demanding conditions. It provides excellent protection against oxidation, wear, and corrosion at high temperatures while maintaining superior multigrade stability and consistent performance.

Benefits

- Protects engine components from varnish and deposit formation.
- High oxidation stability helps limit sludge buildup, promoting longer engine life.
- Offers reliable performance across a wide operating temperature range.

Meets/Exceeds

- API SL
- API SJ

Applications

- Recommended for gasoline engines requiring API SL or lower specifications.
- Developed for vehicles from all international automotive brands.
- Recommended where cold start operation is important.

Product Characteristics

Properties	Test Method	Unit	10W-40
Density at 15 °C	ASTM D4052	kg/L	0.8624
Kinematic Viscosity at 100 °C	ASTM D445	cSt	15.1
Viscosity Index	ASTM D2270	-	156
Flash Point, COC	ASTM D92	°C	232
Pour Point	ASTM D97	°C	-36
Total Base Number	ASTM D2896	mg KOH/g	6.5
<i>Product Code</i>			144042

- Information, test methods, figures are typical and conform to specification; minor variation may occur.
- Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

