

NATIONAL SpeedX Super SPX5 SL

NATIONAL SpeedX Super SPX5 SL series is a high-quality automotive engine oil designed for both modern and legacy gasoline engines. It is formulated with high-performance additive system that ensures reliable operation under demanding conditions. This oil provides superior protection against oxidation, wear, and corrosion at high temperatures, while maintaining excellent stability and performance as a multigrade lubricant.

Benefits

- Protects engine components from varnish and deposit formation.
- High oxidation stability helps limit deposit buildup, promoting longer engine life.
- Offers reliable performance across a wide operating temperature range.

Meets/Exceeds

- API SL
- API SJ

Applications

- Recommended for gasoline engines requiring API SL or lower specifications.
- Developed for vehicles from all international automotive brands.
- SAE 20W-50 viscosity grade is recommended for hot climates and where durability is of prime importance.
- SAE 10W-40 viscosity grade is recommended where cold start operation is important.

Product Characteristics

Properties	Test Method	Unit	SAE 10W-40	SAE 20W-50
Density @ 15 °C	ASTM D4052	kg/L	0.8651	0.8770
Kinematic Viscosity at 100 °C	ASTM D445	cSt	15.1	19.0
Viscosity Index	ASTM D2270	-	155	130
Flash Point, COC	ASTM D92	°C	230	254
Pour Point	ASTM D97	°C	-36	-24
Total Base Number	ASTM D2896	mg KOH/g	6.6	6.6
<i>Product Code</i>			<i>148022</i>	<i>147022</i>

- Information, test methods, figures are typical and conform to specification; minor variation may occur.
- Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

