



PETROMIN Super Ultra 7 SL is a multi-grade engine oil lubricant series designed for current generation passenger car applications. It is specially formulated to surpass the lubrication standards and ensure optimal performance in engines operating under demanding conditions.

Benefits

- Keeps internal engine parts clean by protecting soot, varnish, and deposits.
- Improves engine performance, ensuring smoother operation, greater durability.
- Provides superior oxidation resistance, ensuring oil stability and extended engine performance.
- Delivers good cold-start protection in temperature climates, reducing engine wear and tear at start-up.

Meets/Exceeds

- API SJ

Approvals

- API SL

Applications

- Recommended for use in gasoline engines requiring API SL or lower performance levels.
- Suitable for global gasoline vehicle manufacturers, including American, European and Japanese OEMs.

Product Characteristics

Properties	Test Method	Unit	SAE 10W-40	SAE 15W-40	SAE 20W-50
Density @ 15 °C	ASTM D4052	kg/L	0.8651	0.8710	0.8770
Kinematic Viscosity at 40 °C	ASTM D445	cSt	102.1	110.1	165.6
Kinematic Viscosity at 100 °C	ASTM D445	cSt	15.1	14.7	19.03
Viscosity Index	ASTM D2270	-	155	137	130
Flash Point, COC	ASTM D92	°C	230	230	254
Pour Point	ASTM D97	°C	-36	-33	-24
Total Base Number	ASTM D2896	mg KOH/g	6.5	6.5	6.5
<i>Product Code</i>			<i>148000</i>	<i>157200</i>	<i>147000</i>

* Information, test methods, figures are typical and conform to specification; minor variation may occur.

* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information

