



PETROMIN Super 10W-30 SL is an advanced automotive engine oil for current as well as legacy gasoline engines. It is blended with proven additives that enable it to deliver better performance under challenging operating conditions. It provides effective protection against oxidation, wear, and corrosion under high-temperature operations and remains stable as a multigrade oil.

## Benefits

- Keeps internal engine parts clean by protecting against varnish and deposits.
- Superior oxidation stability reduces high-temperature deposits, thereby improving engine life.
- Provides protection across a wide range of operating temperatures.

## Meets/Exceeds

- API SJ

## Approvals

- API SL

## Applications

- Suitable for both older and newer gasoline engines that require API SL or lower performance levels.
- Recommended for all legacy passenger vehicles.
- Recommended for cold climate operation.

## Product Characteristics

Properties	Test Method	Unit	SAE 10W-30
Density @ 15 °C	ASTM D4052	kg/L	0.8687
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	74.5
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	11.0
Viscosity Index	ASTM D2270	-	137
Flash Point, COC	ASTM D92	°C	228
Pour Point	ASTM D97	°C	-36
Total Base Number	ASTM D2896	mg KOH/g	6.5
<i>Product Code</i>			<i>155000</i>

\* Information, test methods, figures are typical and conform to specification; minor variation may occur.

\* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

\* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information

