



PETROMIN Super Ultra 7 series is an advanced automotive engine oil for current as well as legacy gasoline performance specifications. It is blended with proven additives that enable it to deliver better performance under challenging operating conditions. It provides effective protection against oxidation, wear, and corrosion under high-temperature operations and remains stable as a multigrade oil.

Benefits

- Keeps internal engine parts clean by protecting against varnish and deposits.
- Excellent oxidation stability reduces high-temperature deposits, thereby improving engine life.
- Provides protection across a wide range of operating temperatures.

Meets/Exceeds

- API SJ

Approvals

- API SL

Applications

- Suitable for both older and newer gasoline engines which require API SL or lower performance levels.
- Recommended for all legacy passenger vehicles according to their respective SAE viscosity grade requirements.
- SAE 10W-40 is recommended for cold climate operation.
- SAE 20W-50 is suitable for hot climate operation and for legacy vehicles.

Product Characteristics

Properties	Test Method	Unit	SAE		
			10W-40	15W-40	20W-50
Density @ 15 °C	ASTM D4052	kg/L	0.8662	0.8833	0.8891
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	103.8	110.1	165.6
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	15.2	15.1	19.1
Viscosity Index	ASTM D2270	-	154	143	166
Flash Point, COC	ASTM D92	°C	222	224	238
Pour Point	ASTM D97	°C	-21	-30	-21
Total Base Number	ASTM D2896	mg KOH/g	6.6	6.6	6.5
<i>Product Code</i>			<i>158000</i>	<i>157000</i>	<i>156000</i>

* Information, test methods, figures are typical and conform to specification; minor variation may occur.

* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information

