

# NATIONAL SpeedX SPX5 15W-40

NATIONAL SpeedX SPX5 15W-40 is a high-quality engine oil designed for both modern and legacy gasoline engines. Its advanced additive system delivers dependable performance under demanding conditions, providing excellent protection against oxidation, wear, and corrosion while maintaining stable multigrade performance.

## Benefits

- Safeguard engine components from varnish and sludge deposits.
- Excellent oxidation resistance helps minimize deposit buildup, extending engine life.
- Ensure consistence performance across a wide temperature range.

## Meets/Exceeds

- API SL
- API SJ

## Applications

- Suitable for gasoline engines meeting API SL or earlier specifications.
- Designed for vehicles from all major international automotive brands.
- Ideal for applications where reliable cold-start performance is required.

## Product Characteristics

Properties	Test Method	Unit	15W-40
Density at 15 °C	ASTM D4052	kg/L	0.8710
Kinematic Viscosity at 100 °C	ASTM D445	cSt	14.7
Viscosity Index	ASTM D2270	-	137
Flash Point, COC	ASTM D92	°C	238
Pour Point	ASTM D97	°C	-33
Total Base Number	ASTM D2896	mg KOH/g	6.5
<i>Product Code</i>			157242

- Information, test methods, figures are typical and conform to specification; minor variation may occur.
- Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

