



PETROMIN Tuk Tuk Oil 40 is a dual-fuel engine oil designed for legacy naturally aspirated diesel as well as gasoline engines. It delivers superior performance under demanding conditions, providing excellent protection against wear, corrosion, and high-temperature stress, thereby ensuring longer engine life and optimal performance.

Benefits

- Protects engine components from corrosion and rust, even in humid or harsh conditions.
- Minimize sludge and varnish formation, keeping the engine clean and improving efficiency.
- Reduces sludge, varnish, and carbon deposits, keeping the engine clean.

Meets/Exceeds

- API SF/CD

Applications

- Suitable for Tuk-Tuks, small commercial vehicles, and older passenger cars.
- Ideal for mixed-fleet operations where both gasoline and diesel engines are in use.
- Light-duty on-highway vehicles operating with monograde oils and requiring API SF/CD performance.

Product Characteristics

Properties	Test Method	Unit	SAE 40
Density at 15 °C	ASTM D4052	kg/L	0.8961
Kinematic Viscosity at 40 °C	ASTM D445	cSt	147.1
Kinematic Viscosity at 100 °C	ASTM D445	cSt	14.3
Viscosity Index	ASTM D2270	-	106
Flash Point, COC	ASTM D92	°C	254
Pour Point	ASTM D97	°C	-15
Total Base Number	ASTM D2896	mg KOH/g	5.7
<i>Product Code</i>			183000

* Information, test methods, figures are typical and conform to specification; minor variation may occur.

* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information

