

NATIONAL Tuk Tuk Oil 40 SF/CD

NATIONAL Tuk Tuk Oil 40 SF/CD is a monograde engine oil designed for legacy diesel and gasoline engines, especially those operating in hot climates. It offers reliable protection against wear, deposits, and oxidation. Ideal for mixed fleet operations where a common engine oil is preferred.

Benefits

- Enhanced wear protection for critical engine parts, reducing friction and increasing engine longevity.
- Prevents sludge and carbon buildup, maintaining engine efficiency and reducing maintenance needs.
- Rust and corrosion protection for all engine components, ensuring reliable operation.

Meets/Exceeds

- API SF/CD

Applications

- Suitable for older gasoline and diesel engines.
- Recommended for vehicle requiring API SF/CD or lower performance level.
- Recommended for 3-wheelers where SAE 40 viscosity oil is specified.
- Ideal for mixed fleet operating under severe temperatures conditions.

Product Characteristics

Properties	Test Method	Unit	SAE 40
Density @ 15 °C	ASTM D4052	kg/L	0.8961
Kinematic Viscosity at 40 °C	ASTM D445	cSt	147.1
Kinematic Viscosity at 100 °C	ASTM D445	cSt	15.2
Viscosity Index	ASTM D2270	-	105
Flash Point, COC	ASTM D92	°C	258
Pour Point	ASTM D97	°C	-15
<i>Product Code</i>			<i>183042</i>

- Information, test methods, figures are typical and conform to specification; minor variation may occur.
- Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

