

NATIONAL SpeedX SPX5 20W-50 SL

NATIONAL SpeedX SPX5 20W-50 SL is an automotive engine oil designed to meet the requirements of both modern and legacy gasoline engines. Formulated with carefully balanced base oils and proven additive technology, it delivers consistent performance across a wide range of operating conditions including where fuel Sulphur level is high.

Benefits

- Keeps internal engine parts clean by preventing varnish and deposit build-up.
- Excellent oxidation stability minimizes high temperature deposits and helps in extending engine life.
- Reliable protection across a wide temperature range, ensure consistent performance in varying conditions.

Meets/Exceeds

- API SL
- API SJ

Applications

- Suitable for both modern and older gasoline engines requiring API SL or earlier performance categories.
- Ideal for hot climates and for older vehicles requiring high viscosity oils.
- Designed for optimized drains in high 'S' fuel applications.

Product Characteristics

Properties	Test Method	Unit	20W-50
Density @ 15 °C	ASTM D4052	kg/L	0.8927
Kinematic Viscosity at 100 °C	ASTM D445	cSt	17.8
Kinematic Viscosity at 40 °C	ASTM D445	cSt	178.2
Viscosity Index	ASTM D2270	-	128
Flash Point, COC	ASTM D92	°C	248
Pour Point	ASTM D97	°C	-24
Total Base Number	ASTM D2896	mg KOH/g	9.5
<i>Product Code</i>			<i>197042</i>

- Information, test methods, figures are typical and conform to specification; minor variation may occur.
- Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

