



PETROMIN Diesel HD 2 API CD series is a fit-for-purpose engine oil that offers engine wear protection and keeps it deposit free ensuring dependable engine performance and longevity. The oil is suited for legacy fleet vehicles, off-road machinery, and industrial diesel engines operating in demanding environment. It is suitable for indirect injection, naturally aspirated diesel engines.

Benefits

- Anti-wear property minimizes engine wear and reduces maintenance costs in legacy diesel engines.
- Controls soot and deposits for cleaner engine operation.
- Protects against corrosion in high-sulfur fuel application.

Meets/Exceeds

- API CD

Applications

- Suitable for use in legacy diesel engines requiring API CD or lower performance level.
- Ideal for small trucks, commercial vehicles, vans, tractors, stationary power generation units.
- Compatible with high-sulfur diesel fuels.

Product Characteristics

Properties	Test Method	Unit	HD2 SAE 30	HD2 SAE 50
Density @ 15 °C	ASTM D4052	kg/L	0.8922	0.9026
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	100.3	247
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	11.3	20.5
Viscosity Index	ASTM D2270	-	99	97
Flash Point, COC	ASTM D92	°C	236	282
Pour Point	ASTM D97	°C	-24	-15
Total Base Number	ASTM D2896	mg KOH/g	5.8	5.9
<i>Product Code</i>			<i>223000</i>	<i>225000</i>

* Information, test methods, figures are typical and conform to specification; minor variation may occur.

* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

