



PETROMIN Super DSL Plus 15W-40 CF is designed for legacy naturally aspirated diesel engines to deliver superior performance and protection in a wide range of heavy-duty applications and operating temperatures. It provides excellent wear protection and deposits control, helping to optimize engine durability and efficiency.

Benefits

- Reduces engine wear and protects critical components such as piston, rings, and bearings.
- Enhanced oxidation stability resist oil breakdown at high temperatures
- Multi-grade viscosity profile facilitates oil flow and protects engines from wear at start-up.

Meets/Exceeds

- API CF

Applications

- Suitable for older heavy-duty diesel engines in trucks, buses, and industrial machinery.
- Designed for older diesel engines requiring API CF oils, including trucks, buses, and industrial machinery.
- Suitable for heavy-duty vehicles, off-highway equipment, and stationary engines operating in various conditions, providing reliable protection and performance for a wide range of older diesel applications

Product Characteristics

Properties	Test Method	Unit	SAE 15W-40
Density @ 15 °C	ASTM D4052	kg/L	0.8847
Kinematic Viscosity at 40 °C	ASTM D445	cSt	115.0
Kinematic Viscosity at 100 °C	ASTM D445	cSt	15.5
Viscosity Index	ASTM D2270	-	142
Flash Point, COC	ASTM D92	°C	234
Pour Point	ASTM D97	°C	-30
Total Base Number	ASTM D2896	mg KOH/g	12.3
<i>Product Code</i>			<i>284000</i>

- * Information, test methods, figures are typical and conform to specification; minor variation may occur.
- * Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- * Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

