

PETROMIN Turbo Diesel C 15W-40 CF-4



PETROMIN Turbo Diesel C 15W-40 CF-4 is designed for naturally aspirated diesel engines requiring API CF-4 or lower performance level lubricant. It provides reliable protection against wear, corrosion, and thermal degradation, ensuring dependable engine performance and longevity. The oil is suited for legacy fleet vehicles, off-road machinery, and industrial diesel engines operating in demanding environment.

Benefits

- Provides superior wear protection to components in legacy diesel engines.
- Controls soot and deposits, thereby facilitating cleaner engine operation.
- Provide outstanding thermal and oxidation stability.

Meets/Exceeds

- API CF-4
- API CF

Applications

- Suitable for use in legacy diesel engines requiring API CF or lower performance level.
- Suitable for agricultural, marine and construction machinery.
- Compatible with high-sulfur diesel fuels.
- Preferred choice for fleet operators using monograde oils in legacy and old generation equipment.

Product Characteristics

Properties	Test Method	Unit	SAE 15W-40
Density @ 15 °C	ASTM D4052	kg/L	0.8851
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	117
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	15.6
Viscosity Index	ASTM D2270	-	140
Flash Point, COC	ASTM D92	°C	240
Pour Point	ASTM D97	°C	-30
Total Base Number	ASTM D2896	mg KOH/g	10.3
<i>Product Code</i>			286000

* Information, test methods, figures are typical and conform to specification; minor variation may occur.

* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

