



PETROMIN Flushing Oil is a petroleum mineral oil meant to clean internal engine and lubricant system before an oil change. It removes sludge, varnish, and deposits from gasoline and diesel engines, hydraulic systems, and industrial gearboxes, ensuring optimal cleanliness for fresh lubricant applications.

Benefits

- Dissolves and suspends sludge and deposits from hard-to-reach system components.
- Provides temporary protection to surfaces and components.
- Designed to be drained completely along with contaminants.

Applications

- Suitable for use in engines requiring internal cleaning due to oil contamination or sludge buildup.

Instructions

- Drain the used lubricant completely.
- Refill with PETROMIN Flushing Oil.
- Run the equipment at idle or low speed, without load, for 10-15 minutes to ensure proper circulation. Do not allow extended idling.
- Drain the flushing oil thoroughly while hot/warm.
- Replace the oil filter.
- Refill with the recommended service lubricant.

Product Characteristics

Properties	Test Method	Unit	Flushing Oil
Density @ 15 °C	ASTM D4052	kg/L	0.8739
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	30.5
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	5.2
Viscosity Index	ASTM D2270	-	100
Flash Point, COC	ASTM D92	°C	>200
Pour Point	ASTM D97	°C	-12
<i>Product Code</i>			311000

* Information, test methods, figures are typical and conform to specification; minor variation may occur.

* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

