



PETROMIN ATF Dexron III H is a high performance, multipurpose Automatic Transmission Fluid that covers wide range of passenger and light commercial vehicle requirements. It provides smooth shifting performance and noise free operation for longer operational periods.

Benefits

- Excellent low-temperature fluidity ensures smooth, cold-weather shifting, and ease of startability.
- Outstanding oxidation and thermal stability for long service life.
- Compatible with a wide range of seals and materials used in automatic transmissions.
- Balanced foam control ensures reliable hydraulic performance.

Meets/Exceeds

- General Motors Dexron III H
- Ford Motors Mercon
- Allison C-4

Applications

- Automatic transmissions recommending General Motors Dexron III H / Ford Mercon / Allison C-4 specs.
- Power steering system, servo steering, fluid couplings, and hydrodynamic converters where ATF is specified.
- Hydrostatic drives and hydraulic systems in industrial, agricultural, mining and marine applications.

Not recommended for use in continuously variable transmission (CVT) systems.

Product Characteristics

Properties	Test Method	Unit	ATF Dex III H
Density @ 15 °C	ASTM D4052	kg/L	0.8515
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	36.0
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	7.2
Viscosity Index	ASTM D2270	-	172
Flash Point, COC	ASTM D92	°C	210
Pour Point	ASTM D97	°C	-48
<i>Product Code</i>			331000

* Information, test methods, figures are typical and conform to specification; minor variation may occur.

* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

