

# NATIONAL ATF Dexron III H

NATIONAL ATF Dexron III H is a high performance, multipurpose Automatic Transmission Fluid that covers wide range of passenger and light commercial vehicle requirements. It provides smooth shifting performance and noise free operation for longer operational periods.

## Benefits

- Excellent low-temperature fluidity ensures smooth, cold-weather shifting, and ease of startability.
- Outstanding oxidation and thermal stability for long service life.
- Compatible with a wide range of seals and materials used in automatic transmissions.
- Balanced foam control ensures reliable hydraulic performance.

## Meets/Exceeds

- General Motors Dexron III H
- Ford Motors Mercon
- Allison C-4

## Applications

- Automatic transmissions recommending General Motors Dexron III H / Ford Mercon / Allison C-4 specs.
  - Power steering system, servo steering, fluid couplings, and hydrodynamic converters where ATF is specified.
  - Hydrostatic drives and hydraulic systems in industrial, agricultural, mining and marine applications.
- \* Not recommended for use in continuously variable transmission (CVT) systems.

## Product Characteristics

Properties	Test Method	Unit	ATF Dex III H
Density @ 15 °C	ASTM D4052	kg/L	0.8496
Kinematic Viscosity at 100 °C	ASTM D445	cSt	7.3
Viscosity Index	ASTM D2270	-	177
Flash Point, COC	ASTM D92	°C	230
Pour Point	ASTM D97	°C	-48
<i>Product Code</i>			<b>331042</b>

- Information, test methods, figures are typical and conform to specification; minor variation may occur.
- Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

