

# NATIONAL Super X50 SAE 50 API SJ

## [#395022]

NATIONAL Super X50 SAE 50 API SJ is a mono-grade engine lubricant designed for passenger cars and light-duty gasoline vehicle. It provides reliable oxidation stability and engine cleanliness, making it suitable for vehicles that require API SJ or earlier performance specifications.

### Benefits

- Provides protection against sludge, rust, corrosion, and wear.
- Maintains engine cleanliness by preventing varnish and deposit buildup.
- Lowers friction and helps extend the life of engine components.

### Meets/Exceeds

- API SJ

### Applications

- Suitable for legacy gasoline passenger vehicles requiring API SJ or earlier performance levels.
- Recommended for gasoline-powered three-wheelers equipped with dry clutches.

### Product Characteristics

Properties	Test Method	Unit	SAE 50
Density @ 15 °C	ASTM D4052	kg/L	0.9008
Kinematic Viscosity at 100 °C	ASTM D445	cSt	20.4
Viscosity Index	ASTM D2270	-	104
Flash Point, COC	ASTM D92	°C	262
Pour Point	ASTM D97	°C	-15
<i>Product Code</i>			<i>395022</i>

- Information, test methods, figures are typical and conform to specification; minor variation may occur.
- Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

