

NATIONAL SpeedX Ultra SPX8 0W-16

NATIONAL SpeedX Ultra SPX8 0W-16 is an advanced next-generation, high performance gasoline engine oil. It is formulated to surpass the latest API SP and ILSAC GF-6B gasoline specifications. This premium synthetic lubricant is ideal for modern high-performance engines, including those equipped with emission control systems and hybrid powertrains.

Benefits

- Extends oil change intervals while optimizing fuel efficiency.
- Offers superior engine wear protection under severe driving conditions and across a wide temperature range.
- Keeps internal engine components clean by preventing varnish and deposit formation.
- Delivers excellent cold-start protection, minimizing engine wear during start-up.
- Protects against low-speed pre-ignition (LSPI) commonly observed in modern GDI engines.

Meets/Exceeds

- API SP
- API SN Plus
- API SN
- ILSAC GF-6B

Applications

- Modern gasoline passenger car engines equipped with emission control systems such as SCR and GPF.
- Recommended for all modern gasoline engines from global vehicle manufacturers.
- Suitable for use in all gasoline engines requiring API SP or earlier specifications.

Product Characteristics

Properties	Test Method	Unit	0W-16
Density at 15 °C	ASTM D4052	kg/L	0.8427
Kinematic Viscosity at 100 °C	ASTM D445	cSt	7.9
Kinematic Viscosity at 40 °C	ASTM D445	cSt	38.9
Viscosity Index	ASTM D2270	-	167
Flash Point, COC	ASTM D92	°C	226
Pour Point	ASTM D97	°C	-42
Total Base Number	ASTM D2896	mg KOH/g	7.2
<i>Product Code</i>			429000

- Information, test methods, figures are typical and conform to specification; minor variation may occur.
- Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

