



PETROMIN MP Tractor Oil series is a multi-purpose STOU (Super Tractor Oil Universal) oil designed for use in tractor engines, transmissions, final drives and hydraulic systems. Multifunctional product design covers a wide range of applications in farm equipment as well as off-road applications optimizing inventory and reducing misapplication.

Benefits

- Strong oxidation resistance and built-in detergency keep internal engine parts free from deposits.
- Good EP and anti-wear chemistry offer protection for gears and transmissions from pitting and scuffing.
- Balanced additive chemistry provides smooth, noise-free hydraulic operation.
- Provides cold start protection that significantly reduces engine wear and tear at start-up.

Meets/Exceeds

- API CG-4
- ACEA E3
- API GL-4
- John Deere JD 20C, J27
- Ford M2C 86 B, M2C 86 C, M2C 134 D
- CNH MAT 3525, 3526
- Massey Ferguson MF 1135, M1139, M1145
- Allison C-4
- CAT TO-2
- ZF TE-ML 06A, 06B, 06C, 07B
- Eaton/Vickers M2950S, I-286-S

Applications

- Diesel engines, especially in equipment where a common engine and transmission oil is preferred.
- Powertrain transmissions, drive axles, clutches, PTOs, hydraulic systems, power steering fluids, and oil-immersed brakes operating in agricultural, industrial, and earth-moving equipment.

Product Characteristics

Properties	Test Method	Unit	10W-30	15W-40
Density @ 15 °C	ASTM D4052	kg/L	0.8722	0.8749
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	81.7	113.5
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	12.1	15.0
Viscosity Index	ASTM D2270	-	143	137
Flash Point, COC	ASTM D92	°C	234	238
Pour Point	ASTM D97	°C	-36	-30
<i>Product Code</i>			471000	472000

- * Information, test methods, figures are typical and conform to specification; minor variation may occur.
- * Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- * Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

