



PETROMIN Petromax series is a premium quality high-performance gasoline engine oil, designed to meet the latest engine performance requirement. It also covers the challenging requirements of the latest Gasoline engines including those fitted with Direct Injection (GDI) systems.

Benefits

- Ultimate engine wear protection under wide driving conditions.
- Shields internal engine parts by offering unparalleled protection against soot, varnish, and other deposits.
- Provides easy cold starts and ideal lubrication at elevated temperatures.
- Compatible for use in engines fitted with exhaust emission control systems.
- Protection against low-speed pre-ignition (LSPI) events seen in GDI engines.

Meets/Exceeds

- API SP
- API SN PLUS
- API SN

Applications

- Modern gasoline passenger car engines fitted with emission control devices.
- Suitable for use in all gasoline engines requiring API SP or lower performance.

Product Characteristics

Properties	Test Method	Unit	SAE 10W-30	SAE 15W-40
Density @ 15 °C	ASTM D4052	kg/L	0.8585	0.8725
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	67.67	121.3
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	10.4	15.7
Viscosity Index	ASTM D2270	-	141	137
Flash Point, COC	ASTM D92	°C	226	236
Pour Point	ASTM D97	°C	-36	-30
<i>Product Code</i>			<i>488000</i>	<i>494000</i>

* Information, test methods, figures are typical and conform to specification; minor variation may occur.

* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

