



PETROMIN Compressor Oil S 68 is an advanced compressor oil designed to meet the requirements of the latest screw compressors. Carefully selected chemistry ensures consistent performance in diverse operating conditions around the clock. It exceeds major OEM requirements.

## Benefits

- Excellent air-sealing, air-release, and foam-inhibition properties boost system efficiency and compressor performance.
- Superior anti-wear capability protects components and extends equipment service life.
- Exceptional oxidation stability helps prolong oil drain intervals.
- Built-in rust and corrosion inhibitors protect piston crowns, valves, and other internal components.

## Meets/Exceeds

- DIN 51506 VDL
- ISO 6743-3 DAA, DAB, DAH

## Applications

- Stationary and mobile air compressors operating in severe conditions.
- Rotary, screw, reciprocating, and vane compressors.
- As a circulation oil for lightly loaded gears and plain bearings.

## Product Characteristics

Properties	Test Method	Unit	ISO VG 68
Density @ 15 °C	ASTM D4052	kg/L	0.8629
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	67.9
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	9.5
Viscosity Index	ASTM D2270	-	119
Flash Point, COC	ASTM D92	°C	240
Pour Point	ASTM D97	°C	-24
<i>Product Code</i>			<b>540000</b>

- \* Information, test methods, figures are typical and conform to specification; minor variation may occur.
- \* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- \* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

