

# PETROMIN Super Brake Fluid DOT 3

PETROMIN Super Brake Fluid DOT 3 is a high-performance hydraulic brake fluid designed for use in automotive disc, drum, anti-skid brake, and clutch systems. Engineered to deliver consistent brake response, it helps ensure safety and reliability across a wide range of driving conditions. Enhanced with corrosion inhibitors and performance stabilizers, it provides excellent protection for critical brake components and resists vapor lock, even under high operating temperatures.

## Benefits

- Provides stable performance across a wide range of operating temperatures.
- High boiling point reduces the risk of brake fading.
- Maintains brake fluid cleanliness and system reliability.
- Compatible with rubber seals and hoses.

## Meets/Exceeds

- FMVSS No. 116
- SAE J 1703

## Applications

- Recommended for use in hydraulic disc, drum, ABS brake systems, and clutch systems in passenger cars and commercial vehicles where DOT 3 performance is required.
- Not suitable for systems requiring mineral oil or silicone-based fluids.

## Product Characteristics

Properties	Test Method	Unit	DOT 3
Density @ 20 °C	ASTM D4052	kg/L	1.08
Kinematic Viscosity at -40°C, max	ASTM D7042	cSt	1500
Kinematic Viscosity at 100°C, min	ASTM D445	cSt	1.5
Equilibrium reflux boiling point, min	ASTM D 1120	-	205
pH	ASTM D1287	°C	7 to 11.5
<i>Product Code</i>			<i>564100</i>

\* Information, test methods, figures are typical and conform to specification; minor variation may occur.

\* Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.

\* Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

