

PETROMIN Anti-Freeze Coolant 500 (Green)



PETROMIN Anti-Freeze Coolant 500 (Green) is designed for use in the liquid cooling systems of automotive engines and industrial machinery, particularly for older vehicles and conventional cooling systems. Utilizing traditional chemistry, it provides protection against freezing, boiling, and corrosion. Engineered for optimal heat transfer, this coolant ensures reliable and efficient engine operation across a wide range of temperatures.

Benefits

- Protects the radiator against rust, corrosion, and excessive evaporation.
- Provides reliable year-round cooling performance with anti-freeze properties.
- Compatible with ordinary market general coolants.

Applications

- Suitable for use in older vehicles and conventional cooling systems.
- Recommended for both light and heavy-duty vehicles, particularly older vehicles.
- Cooling systems of industrial machinery where a fit-for-purpose coolant is required.
- Ready-to-use (RTU) and should not be further diluted.

Product Characteristics

Properties	Test Method	Unit	500
Color	Visual	-	Green
Freezing Point	ASTM D3321	°C	-38
Equilibrium Boiling Point	ASTM D1120	°C	108
Glycol Concentration	ASTM D3306	%	50
Density @ 20°C	ASTM D4052	kg/L	1.068
Reserve Alkalinity	ASTM D1121	ml	Report
pH	ASTM D1287		7.9
<i>Product Code</i>			<i>595100</i>

- * Information, test methods, figures are typical and conform to specification; minor variation may occur.
- * Refer Owner's Manual for the manufacturer's recommended performance level, viscosity grade and builder approval requirements.
- * Please refer to the product Safety Data Sheet (SDS) for health, safety, and handling information.

